

Package: assert (via r-universe)

September 17, 2024

Title Validate Function Arguments

Version 1.0.1

Description Lightweight validation tool for checking function arguments and validating data analysis scripts. This is an alternative to stopifnot() from the 'base' package and to assert_that() from the 'assertthat' package. It provides more informative error messages and facilitates debugging.

URL <https://github.com/OlivierBinette/assert>

BugReports <https://github.com/OlivierBinette/assert/issues>

License GPL (>= 2)

Encoding UTF-8

LazyData true

ByteCompile true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

Repository <https://olivierbinette.r-universe.dev>

RemoteUrl <https://github.com/olivierbinette/assert>

RemoteRef HEAD

RemoteSha c0de371fa3c76d052e2b45d64592a9311c54a92c

Contents

assert	2
Index	4

assert *Assertions and Argument Validation*

Description

Assert that each of the provided expression is true. Otherwise stop execution and return a description of each failed assertion.

Usage

```
assert(..., msg = "", stop = TRUE)
```

Arguments

...	List of logical assertions.
msg	Message to print alongside the list of failed assertions (if any).
stop	Whether execution should be stopped on failed assertions. If set to FALSE, then only a warning is issued. Default is TRUE.

Value

Nothing if all assertions pass. Otherwise throws an error describing which

Examples

```
attach(ChickWeight)

# Passing assertions
assert(is.numeric(weight),
       all(weight > 0))

# Failing assertions
if (interactive()) {
  assert(all(Diet > 0),
         is.numeric(Times))
}

# Validating function arguments
sum <- function(a, b) {
  assert(is.numeric(a),
         is.numeric(b),
         length(a) == length(b))

  return(a+b)
}

sum(2, 2)

if (interactive()) {
```

assert

3

```
sum("1", 2)  
sum(1, c(1,2))  
sum(1, x)  
}
```

Index

assert, [2](#)